

Product Information

Product Brand: Roto Solid

Roto Solid C - Accessories

Opening damper



Related Products

Roto Solid

Other

Scope

- The opening damper from the Roto AL hardware range (arrestable, damped, see PI 2014/2174) can also be used on doors in conjunction with Roto Solid C.
- Can be used in aluminium profiles with V.01 or V.02 frame groove
- The opening damper should be installed at the top of the sash. See IMO_163 for further details on installation.
- Approved for 25000 cycles according to DIN EN 13126-5
- Internally tested in endurance run with 200.000 cycles (at 100kg sash weight) according to DIN EN 1191
- Relief of the hinge parts by end position damping in the open position
- **The opening damper is a comfort component for damping the opening movement and has no hard end stop.**
- **It is not possible to limit the opening angle to fix the sash at e.g. 100°.**
- **An additional component (e.g. door stop) must be used to limit the opening angle.**

Documentation

see IMO_163

Product Overview

Material No.	EAN no.	Description	PU	Price/Pcs.	Material Size	D-MG	Spout Material
774487	4036263285324	AL DRB SET G1 V1 GED					

774484 4036263285713 AL DRB SET G1 V2 GED

774495 4036263285720 AL DRB SET G2 V1 GED

774496 4036263285737 AL DRB SET G2 V2 GED

More Pictures:

