

Product Information

Roto AL | TiltSafe (v1)

Security for tilted windows



New product

Scope

As of now, Tilt&Turn windows, in combination with the hinge side AL Designo, can be equipped with the new TiltSafe security strikers.

As usual, closed aluminum windows, depending on the hardware configuration, meet the requirement of known security classes.

Elements equipped with TiltSafe now also meet the requirement for security class RC2 when tilted.

- Burglar resistance for tilted windows, according to RC2, through three TiltSafe security strikers.

- Up to 85 mm tilt width

- Usual simple operation without restriction

Technical Details

- Can be used with hinge side AL Designo up to 150 kg

- Up to a sash width of 1,300 mm

- Up to a sash height of 2,700 mm

- For a weight of up to 150 kg

- Min. installation space (frame) >26.5 mm

- For installation space (frame) < 26.5 mm, a profile check must be carried out

- Additional document IMO_386



Created on 09.03.2021
Modified on 09.03.2021

No. 18 2174

Availability / Ordering ability - Available from week 12

Product Overview

Material No.	EAN no.	Description	PU	Price/Pcs.	Material Si ze	D-MG	Spout Mater ial
891050	4018609237327	AL TILTSAFE SET R	10	88,90	3K		
891051	4018609237334	AL TILTSAFE SET L	10	88,90	3K		
891052	4018609237341	AL TILTSAFE tilt striker V1	10	11,58	3K		
891053	4018609237358	AL TILTSAFE tilt striker V2	10	11,57	3K		
891318	4018609237464	AL TILTSAFE locking parts SET V1	10	33,27	3K		
891365	4018609237471	AL TILTSAFE locking parts SET V2	10	33,27	3K		