

## Product Information

Product Brand: Roto Solid

Roto Solid B for timber profiles



### Related Products

Roto Solid  
New product

### Application range

The new Roto Solid B butt hinge family for PVC doors can now also be used in timber profiles.

#### Rebate screwed

A new variant for 318 P and 322 P with a shorter sash hinge body was set up for assembly in the rebate (RS IV).

- Hardware groove: 16 mm in the sash
- min. rebate depth: 24 mm
- axis: 8 - 15 mm
- Rebate clearance: 12 mm

#### Overlap screwed

The existing OS I variant can be used for installation in the overlap.

- min. Overlap height: 16.5 mm (depending on profile and seal)

#### General notes

- The sash weights and application areas remain unchanged.
- Generally, a profile check is necessary in advance.

#### Notes on wood species

The VFF leaflet HO.06-1 "Types of wood for window construction" and EN 14351-1 must be observed.

The guideline values for raw densities can be taken from the leaflet. (recommendation > 0.43 g/cm<sup>3</sup>)

### Documentation

- CTL\_88
- IMO\_568, IMO\_570
- IMO\_569

## Availability / Ordering ability

- Available for order immediately
- First delivery approx. 2-3 weeks after order

## Product Overview

Material No.	EAN no.	Description	PU	Price/Pcs.	Material Si ze	D-MG	Spout Mater ial
2028879	9005904400919	318 P RS IV R01.1 L VE1	1				
2028880	9005904400926	318 P RS IV R01.1 R VE1	1				
2028881	9005904400933	322 P RS IV R01.1 L VE1	1				
2028882	9005904400940	322 P RS IV R01.1 R VE1	1				
2028883	9005904400957	318 P RS IV STS-OPTIK L VE1	1				
2028884	9005904400964	318 P RS IV STS-OPTIK R VE1	1				
2028885	9005904400971	322 P RS IV STS-OPTIK L VE1	1				
2028886	9005904400988	322 P RS IV STS-OPTIK R VE1	1				