

RPI_24_0099 Aug 8, 2024

Product Information Schüco CT70 and Living 82AD/MD

Reinforced version of threshold holder



Overview

System Door

Product Roto Eifel

Tailor-made range of thresholds for tightly sealed accessible doors and balcony doors

Availability / Ordering ability Orderable

Documentation

Description

- Reinforcement of the walls of the threshold holder to prevent the screws from breaking out when tightening.
- An additional centering hook that connects the threshold holder to the frame profile in a torsion-resistant manner, even outside the screwing area.
- Anti-twisting devices and additional screwing options ensure a stable connection between the threshold holder and the floor threshold
- A seal for the threshold is located on the connection side of the threshold holder
- With cover caps to cover the screw holes
- Can be used for all frame and post profiles with the same rebate geometry, as the connection is in the rebate area
- Threshold holder made of thermoplastic PC/ASA --->Components made of PC/ASA must not be brought into contact with cutting oil.

- Delivery without fastening screws \rightarrow Screwing suggestion threshold holder to threshold: Countersunk screw Ø 3.5 x 50 see PI 20 1444.
- Matched with Eifel TB thresholds.
- Suitable with Eifel TB tilt bearing
- Suitable with Designo II corner bearing
- Suitable with Designo II base for Eifel TB threshold (771917 / 771918)

Article Overview

Article Code	EAN No.	Unit	Material Group
2036785 SH 70TB SC CT 70 FALZ RAL 7004 5P STR	4018609255475		1507
2036786 SH FALZ. SC LIVING 82AD RAL 7004 5P STR	4018609255482	0	1507
2036787 SH FALZ. SC LIVING 82MD RAL 7004 5P STR	4018609255499	0	1507

Roto Frank Fenster- und Türtechnologie GmbH

Wilhelm-Frank-Platz 1 70771 Leinfelden-Echterdingen Deutschland